Seat Belt for Forklift

Forklift Seat Belts - Described in the Regulation guidelines are the use of operative restraints and seatbelts on forklifts. It says that the liability falls on the employers' to make certain that each machinery, piece of equipment and tool is used correctly used in accordance to the directions of the producer.

In regards to their maintenance, inspection, fabrication, use and design Rough Terrain lift trucks ought to meet the regulations of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile equipment with a Rollover Protective Structure, or ROPS for short, need to have seat belts that meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile equipment has seat belts required by law, the operator and subsequent passengers must make sure they utilize the belts each time the vehicle is in motion or engaged in operation for the reason that this could cause the machine to become unstable and thus, unsafe.

If a seat belt or other operator restraint is required on a lift truck.

While operating a lift truck, the seat belt requirements will depend on some factors. Contributing factors to this determination might include whether or not the the lift truck is equipped along with a Rollover Protective Structure, the kind of lift truck itself and the year the lift truck was actually manufactured. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, system, or enclosure. An operator restraint device, system, or enclosure is designed so as to assist the operator in lessening the possibility of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device could consist of a seat belt, while a seat belt is not essentially a part of such device or system.